

ASSEMBLY INSTRUCTIONS AND OPERATIONAL SAFETY GUIDE NON-COMPLIANCE WITH GUIDELINES MAY RESULT IN SERIOUS INJURY OR DEATH

Safety Guidelines



Do not begin assembly until you have fully read these instructions Thoroughly Read: https://www.osha.gov/Publications/osha3150.pdf

Never over extend when opening hatch.

- Hatch strap is designed to not stay open for safety reasons.
- Do not force hatch to stay open.

- Make sure hatch is firmly down and the latch is engaged before stepping on hatch. Failure to do so could break latch or cause injurv.
- **Metal Conducts Electricity** Avoid use of unit near or in contact of nower lines or live lactrical cources



Weight Capacity

This Unit was designed for a maximum capacity load of 1.111 LBS 504 kg). Weight Capacity DECREASES with stacking. Only use caffoldmart outriggers and stacking units.

Please visit https://www.osha.gov/Publications/osha3150.pdf to get intimately familiar with the OSHA guidelines and strictly follow them to prevent injury, damage and death.

Remove from box and inspect for damage before every use. Do not use a bent or damaged walkboard.



Place walkboard in side rail grooves. **Confirm it is firmly seated** all the way down on each side.

PART CODE:

MF379HATCH

CUSTOMER SERVICE: 1 (866) 900-0983

customerservice@scaffoldmart.com scaffoldmart.com

- **3 Install spring latch and firmly secure both** sides of walkhoard to multifunction unit.
- 4 Secure hatch latch before walking on walkboard.



ONE YEAR WARRANT